

German Module for the datetime2 Package

<https://github.com/SFr682k/datetime2-german>

Nicola L. C. Talbot
(inactive)

Sebastian Friedl
sfr682k@t-online.de

2017-10-03 (v2.0)

Abstract

This is the German language module for the datetime2 package. If you want to use the settings in this module you must install it in addition to installing datetime2. If you use babel or polyglossia, you will need this module to prevent them from redefining \today. The datetime2 useregional setting must be set to text or numeric for the language styles to be set. Alternatively, you can set the style in the document using \DTMsetstyle, but this may be changed by \date<language> depending on the value of the useregional setting.

Currently there is a regionless style as well as variant styles (de-DE, de-AT and de-CH).

I'm only capable of German standard German. If I messed up anything in regards to format and/or spelling, or even a variant style with differences to the existing ones is missing, please create a feature request on GitHub or send me an e-mail.

I would be very grateful, if some examples and/or a list of the weekdays' and months' spelling is/are also provided.

Thanks to Jürgen Spitzmüller for his valuable advice while developing Version 2.0 of this module.

Contents

1	Installation	3
I	The Documentation	4
2	Setting up datetime2 with a language module	4
2.1	Loading a language module	4
2.2	Other features	4
2.2.1	Showing the weekday	4
2.2.2	Using abbreviated weekday and month names	5
3	Style examples	5
3.1	Regionless style	5
3.2	German style (de-DE)	5
3.3	Austrian style (de-AT)	5
3.4	Swiss style (de-CH)	5
4	Further customization of styles	6
5	License	6
II	The Code	7
6	Basic German module	7
6.1	Weekday and month names (UTF-8)	7
6.2	Weekday and month names (ASCII)	10
6.3	Basic German Module (datetime2-german.ldf)	14
7	German localization (de-DE, datetime2-de-DE.ldf)	19
8	Austrian German localization (de-AT, datetime2-de-AT.ldf)	24
9	Swiss German localization (de-CH, datetime2-de-CH.ldf)	28
	Change History	33
	Index	33

1 Installation

Extract the language definition files first:

1. Run \LaTeX over the file `datetime2-german.ins`:
`latex datetime2-german.ins`
2. Move all `*.ldf` files to `TEXMF/tex/latex/datetime2-contrib/datetime2-german/`

Then, you can compile the documentation yourself by executing

```
pdflatex datetime2-german.dtx
makeindex -s gind.ist datetime2-german.idx
makeindex -s gglo.ist -o datetime2-german.gls datetime2-german.glo
pdflatex datetime2-german.dtx
pdflatex datetime2-german.dtx
```

or just use the precompiled documentation shipped with the source files.

In both cases, copy the files `datetime2-german.pdf` and `README.md` to `TEXMF/doc/latex/datetime2-contrib/datetime2-german/`

File I

The Documentation

2 Setting up datetime2 with a language module

2.1 Loading a language module

There are three different ways to load the required language module. See the datetime2 documentation for further details

Variant 1:

Request the desired language module explicitly by passing the `german`, `de-DE`, `de-AT` or `de-CH` option to the `datetime2` package:

```
\documentclass{article}
\usepackage[german]{datetime2}
\begin{document}
\today
\end{document}
```

Variant 2:

Load `babel` and pass the `german`, `austrian` or `swissgerman` option to the `\documentclass` command (or to `babel` directly). If you now pass the `useregional` option to `datetime2`, the language module suitable to the one specified with `babel` is loaded:

```
\documentclass[german]{article}
\usepackage{babel}
\usepackage[useregional]{datetime2}
\begin{document}
\today
\end{document}
```

Variant 3:

When using `polyglossia`, you should request the desired language module by passing the `german`, `de-DE`, `de-AT` or `de-CH` option to the `datetime2` package:

```
\documentclass{article}
\usepackage{polyglossia}
\setmainlanguage{german}
\usepackage[german]{datetime2}
\begin{document}
\today
\end{document}
```

2.2 Other features

2.2.1 Showing the weekday

All language modules shipped with `datetime2-german` support showing the weekday. To enable this feature, pass the `showdow` option to the `datetime2` package. Please note, that this has no effect when using the `numeric` style of the `de-AT` variant.

2.2.2 Using abbreviated weekday and month names

To enable abbreviated weekday and month names, use `\DTMlangsetup[german]{abbr}`.
To disable them, use `\DTMlangsetup[german]{abbr=false}`.

In both cases, replace `german` with the used variant style (`de-DE`, `de-AT` or `de-CH`).
Please note, that this has no effect when using the numeric style of the `de-AT` variant.

3 Style examples

3.1 Regionless style

- Non-numeric style:
3. Oktober 2017, 12:51:04 MESZ
3. Okt. '17, 12:51:04 MESZ *abbreviated version*
Dienstag, 3. Oktober 2017, 12:51:04 MESZ *with showdow option*
Di, 3. Okt. '17, 12:51:04 MESZ *abbreviated version with showdow option*
- Numeric style:
03.10.2017, 12:51:04 MESZ
03.10.17, 12:51:04 MESZ *abbreviated version*
Dienstag, 03.10.2017, 12:51:04 MESZ *with showdow option*
Di, 03.10.17, 12:51:04 MESZ *abbreviated version with showdow option*

3.2 German style (de-DE)

- Non-numeric style:
3. Oktober 2017, 12:51:04 MESZ
3. Okt. '17, 12:51:04 MESZ *abbreviated version*
Dienstag, 3. Oktober 2017, 12:51:04 MESZ *with showdow option*
Di, 3. Okt. '17, 12:51:04 MESZ *abbreviated version with showdow option*
- Numeric style:
03.10.2017, 12:51:04 MESZ
03.10.17, 12:51:04 MESZ *abbreviated version*
Dienstag, 03.10.2017, 12:51:04 MESZ *with showdow option*
Di, 03.10.17, 12:51:04 MESZ *abbreviated version with showdow option*

3.3 Austrian style (de-AT)

- Non-numeric style:
3. Oktober 2017, 12:51:04 MESZ
3. Okt. 2017, 12:51:04 MESZ *abbreviated version*
Dienstag, 3. Oktober 2017, 12:51:04 MESZ *with showdow option*
Di, 3. Okt. 2017, 12:51:04 MESZ *abbreviated version with showdow option*
- Numeric style:
2017-10-03, 12:51:04 MESZ

3.4 Swiss style (de-CH)

- Non-numeric style:
3. Oktober 2017, 12.51.04 Uhr MESZ

3. Okt. 2017, 12.51.04 Uhr MESZ	<i>abbreviated version</i>
Dienstag, 3. Oktober 2017, 12.51.04 Uhr MESZ	<i>with showdow option</i>
Di, 3. Okt. 2017, 12.51.04 Uhr MESZ	<i>abbreviated version with showdow option</i>
• Numeric style:	
03.10.2017, 12.51.04 Uhr MESZ	
03.10.17, 12.51.04 Uhr MESZ	<i>abbreviated version</i>
Dienstag, 03.10.2017, 12.51.04 Uhr MESZ	<i>with showdow option</i>
Di, 03.10.17, 12.51.04 Uhr MESZ	<i>abbreviated version with showdow option</i>

4 Further customization of styles

There are a number of settings provided that can be used in `\DTMLangsetup` to modify the date-time style. These are:

dowdaysep The separator between the day of week name and the day of month number.

daymonthsep The separator between the day and the month name

monthyearsep The separator between the month name and year

datesep The separator between the date numbers in the numeric styles

timesep The separator between hours, minutes and seconds

datetimesep The separator between the date and time for the full date-time format

timezonese The separator between the time and zone for the full date-time format

abbr This is a boolean key. If true, the month (and weekday name, if shown) is abbreviated.

mapzone This is a boolean key. If true, the time zone mappings are applied.

showdayofmonth A boolean key that determines whether or not to show the day of the month

showyear A boolean key that determines whether or not to show the year

Although the keys listed here are *defined* for all variant styles, it depends on `datetime2`'s setup and the requested styles whether they're *used*.

For more information about the `\DTMLangsetup` command see the documentation of the main `datetime2` package.

5 License

This material is subject to the \TeX Project Public License, Version 1.3c or later. See the copyright headers of the single files for further details.

File II

The Code

6 Basic German module

This module defines the “basic” German style, which contains the necessary vocab for all German localizations.

The date and time format is based on the de-DE variant.

6.1 Weekday and month names (UTF-8)

This file contains the settings that use UTF-8 characters. This file is loaded if Xe_{La}TeX or Lua_{La}TeX are used. Please make sure your text editor is set to UTF-8 if you want to view this code.

Identify module

```
1 \ProvidesDateTimeModule{german-utf8}[2017/10/03 v2.0]
```

\DTMgermanordinal

```
2 \newcommand*{\DTMgermanordinal}[1]{%
3   \number#1
4 }
```

\DTMgermanmonthname German month names.

```
5 \newcommand*{\DTMgermanmonthname}[1]{%
6   \ifcase#1
7   \or
8   Januar%
9   \or
10  Februar%
11  \or
12  März%
13  \or
14  April%
15  \or
16  Mai%
17  \or
18  Juni%
19  \or
20  Juli%
21  \or
22  August%
23  \or
24  September%
25  \or
26  Oktober%
27  \or
28  November%
29  \or
30  Dezember%
31  \fi
32 }
```

\DTMdeATmonthname Austrian German month names. Spot the difference :D

```
33 \newcommand*{\DTMdeATmonthname}[1]{%
```

```

34 \ifcase#1
35 \or
36 Jänner%
37 \or
38 Februar%
39 \or
40 März%
41 \or
42 April%
43 \or
44 Mai%
45 \or
46 Juni%
47 \or
48 Juli%
49 \or
50 August%
51 \or
52 September%
53 \or
54 Oktober%
55 \or
56 November%
57 \or
58 Dezember%
59 \fi
60 }

```

\DTMgermanshortmonthname Abbreviated German month names.

```

61 \newcommand*{\DTMgermanshortmonthname}[1]{%
62 \ifcase#1
63 \or
64 Jan.%
65 \or
66 Feb.%
67 \or
68 März%
69 \or
70 Apr.%
71 \or
72 Mai%
73 \or
74 Juni%
75 \or
76 Juli%
77 \or
78 Aug.%
79 \or
80 Sept.%
81 \or
82 Okt.%
83 \or
84 Nov.%
85 \or
86 Dez.%
87 \fi
88 }

```

\DTMdeATshortmonthname Abbreviated Austrian German month names.

```

89 \newcommand*{\DTMdeATshortmonthname}[1]{%
90   \ifcase#1
91   \or
92   Jän.%
93   \or
94   Feb.%
95   \or
96   März%
97   \or
98   Apr.%
99   \or
100  Mai%
101  \or
102  Juni%
103  \or
104  Juli%
105  \or
106  Aug.%
107  \or
108  Sept.%
109  \or
110  Okt.%
111  \or
112  Nov.%
113  \or
114  Dez.%
115  \fi
116 }
```

\DTMdeCHshortmonthname Abbreviated Swiss German month names.

```

117 \newcommand*{\DTMdeCHshortmonthname}[1]{%
118   \ifcase#1
119   \or
120   Jan.%
121   \or
122   Febr.%
123   \or
124   März%
125   \or
126   April%
127   \or
128   Mai%
129   \or
130   Juni%
131   \or
132   Juli%
133   \or
134   Aug.%
135   \or
136   Sept.%
137   \or
138   Okt.%
139   \or
140   Nov.%
141   \or
```

```

142 Dez.%
143 \fi
144 }

```

`\DTMgermanweekdayname` Provides weekday names

```

145 \newcommand*{\DTMgermanweekdayname}[1]{%
146   \ifcase#1
147   Montag%
148   \or
149   Dienstag%
150   \or
151   Mittwoch%
152   \or
153   Donnerstag%
154   \or
155   Freitag%
156   \or
157   Samstag%
158   \or
159   Sonntag%
160   \fi
161 }

```

`\DTMgermanshortweekdayname` Provides abbreviated weekday names

```

162 \newcommand*{\DTMgermanshortweekdayname}[1]{%
163   \ifcase#1
164   Mo%
165   \or
166   Di%
167   \or
168   Mi%
169   \or
170   Do%
171   \or
172   Fr%
173   \or
174   Sa%
175   \or
176   So%
177   \fi
178 }

```

6.2 Weekday and month names (ASCII)

This file contains the settings that use \TeX commands for non-ASCII characters. This should be input if neither \XeTeX nor \LuaTeX are used. Even if the user has loaded `inputenc` with `utf8`, this file should still be used not the `datetime2-german-utf8.ldf` file as the non-ASCII characters are made active in that situation and would need protecting against expansion.

Identify module

```

179 \ProvidesDateTimeModule{german-ascii}[2017/10/03 v2.0]

```

`\DTMgermanordinal`

```

180 \newcommand*{\DTMgermanordinal}[1]{%
181   \number#1
182 }

```

\DTMgermanmonthname German month names.

```

183 \newcommand*{\DTMgermanmonthname}[1]{%
184   \ifcase#1
185   \or
186   Januar%
187   \or
188   Februar%
189   \or
190   M\protect\"arz%
191   \or
192   April%
193   \or
194   Mai%
195   \or
196   Juni%
197   \or
198   Juli%
199   \or
200   August%
201   \or
202   September%
203   \or
204   Oktober%
205   \or
206   November%
207   \or
208   Dezember%
209   \fi
210 }

```

\DTMdeATmonthname Austrian German month names.

```

211 \newcommand*{\DTMdeATmonthname}[1]{%
212   \ifcase#1
213   \or
214   J\protect\"anner%
215   \or
216   Februar%
217   \or
218   M\protect\"arz%
219   \or
220   April%
221   \or
222   Mai%
223   \or
224   Juni%
225   \or
226   Juli%
227   \or
228   August%
229   \or
230   September%
231   \or
232   Oktober%
233   \or
234   November%
235   \or

```

```

236 Dezember%
237 \fi
238 }

```

`\DTMgermanshortmonthname` Abbreviated German month names.

```

239 \newcommand*{\DTMgermanshortmonthname}[1]{%
240   \ifcase#1
241   \or
242   Jan.%
243   \or
244   Feb.%
245   \or
246   M\protect\"arz%
247   \or
248   Apr.%
249   \or
250   Mai%
251   \or
252   Juni%
253   \or
254   Juli%
255   \or
256   Aug.%
257   \or
258   Sept.%
259   \or
260   Okt.%
261   \or
262   Nov.%
263   \or
264   Dez.%
265   \fi
266 }

```

`\DTMdeATshortmonthname` Abbreviated Austrian German month names.

```

267 \newcommand*{\DTMdeATshortmonthname}[1]{%
268   \ifcase#1
269   \or
270   J\protect\"an.%
271   \or
272   Feb.%
273   \or
274   M\protect\"arz%
275   \or
276   Apr.%
277   \or
278   Mai%
279   \or
280   Juni%
281   \or
282   Juli%
283   \or
284   Aug.%
285   \or
286   Sept.%
287   \or

```

```

288 Okt.%
289 \or
290 Nov.%
291 \or
292 Dez.%
293 \fi
294 }

```

\DTMdeCHshortmonthname Abbreviated Swiss German month names.

```

295 \newcommand*{\DTMdeCHshortmonthname}[1]{%
296 \ifcase#1
297 \or
298 Jan.%
299 \or
300 Febr.%
301 \or
302 M\protect\"arz%
303 \or
304 April%
305 \or
306 Mai%
307 \or
308 Juni%
309 \or
310 Juli%
311 \or
312 Aug.%
313 \or
314 Sept.%
315 \or
316 Okt.%
317 \or
318 Nov.%
319 \or
320 Dez.%
321 \fi
322 }

```

\DTMgermanweekdayname Provides weekday names

```

323 \newcommand*{\DTMgermanweekdayname}[1]{%
324 \ifcase#1
325 Montag%
326 \or
327 Dienstag%
328 \or
329 Mittwoch%
330 \or
331 Donnerstag%
332 \or
333 Freitag%
334 \or
335 Samstag%
336 \or
337 Sonntag%
338 \fi
339 }

```

`\DTMgermanshortweekdayname` Provides abbreviated weekday names

```

340 \newcommand*{\DTMgermanshortweekdayname}[1]{%
341   \ifcase#1
342     Mo%
343   \or
344     Di%
345   \or
346     Mi%
347   \or
348     Do%
349   \or
350     Fr%
351   \or
352     Sa%
353   \or
354     So%
355   \fi
356 }
```

6.3 Basic German Module (`datetime2-german.1df`)

Identify Module

```
357 \ProvidesDateTimeModule{german}[2017/10/03 v2.0]
```

Need to find out if \XeTeX or \LuaTeX are being used.

```
358 \RequirePackage{ifxetex,ifluatex}
```

\XeTeX and \LuaTeX natively support UTF-8, so load `german-utf8` if either of those engines are used otherwise load `german-ascii`.

```

359 \ifxetex
360   \RequireDateTimeModule{german-utf8}
361 \else
362   \ifluatex
363     \RequireDateTimeModule{german-utf8}
364   \else
365     \RequireDateTimeModule{german-ascii}
366   \fi
367 \fi
```

Define the german style.

Allow the user a way of configuring the german and german-numeric styles. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

<code>\DTMgermandowdaysep</code>	The separator between weekday and day
	<pre>368 \newcommand*{\DTMgermandowdaysep}{, \space}</pre>
<code>\DTMgermandaymonthsep</code>	The separator between the day and month for the text format.
	<pre>369 \newcommand*{\DTMgermandaymonthsep}{. \DTMtexorpdfstring{\protect~}{\space}}</pre>
<code>\DTMgermanmonthyearsep</code>	The separator between the month and year for the text format.
	<pre>370 \newcommand*{\DTMgermanmonthyearsep}{\space}</pre>
<code>\DTMgermandatetimesep</code>	The separator between the date and time blocks in the full format (either text or numeric).
	<pre>371 \newcommand*{\DTMgermandatetimesep}{, \space}</pre>
<code>\DTMgermantimezonesep</code>	The separator between the time and zone blocks in the full format (either text or numeric).
	<pre>372 \newcommand*{\DTMgermantimezonesep}{\space}</pre>

\DTMgermandatesep The separator for the numeric date format.

```
373 \newcommand*{\DTMgermandatesep}{.}
```

\DTMgermantimesep The separator for the numeric time format.

```
374 \newcommand*{\DTMgermantimesep}{:}
```

Provide keys that can be used in \DTMlangsetup to set these separators.

```
375 \DTMdefkey{german}{dowdaysep}{\renewcommand*{\DTMgermandowdaysep}{#1}}
376 \DTMdefkey{german}{daymonthsep}{\renewcommand*{\DTMgermandaymonthsep}{#1}}
377 \DTMdefkey{german}{monthyearsep}{\renewcommand*{\DTMgermanmonthyearsep}{#1}}
378 \DTMdefkey{german}{datetimesep}{\renewcommand*{\DTMgermandatetimesep}{#1}}
379 \DTMdefkey{german}{timezonesep}{\renewcommand*{\DTMgermantimezonesep}{#1}}
380 \DTMdefkey{german}{datesep}{\renewcommand*{\DTMgermandatesep}{#1}}
381 \DTMdefkey{german}{timesep}{\renewcommand*{\DTMgermantimesep}{#1}}
```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
382 \DTMdefboolkey{german}{abbr}[true]{}
```

The default is full name

```
383 \DTMsetbool{german}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
384 \DTMdefboolkey{german}{mapzone}[true]{}
```

The default is to use mappings.

```
385 \DTMsetbool{german}{mapzone}{true}
```

Define a boolean key that determines if the day of month should be displayed.

```
386 \DTMdefboolkey{german}{showdayofmonth}[true]{}
```

The default is to show the day of month.

```
387 \DTMsetbool{german}{showdayofmonth}{true}
```

Define a boolean key that determines if the year should be displayed.

```
388 \DTMdefboolkey{german}{showyear}[true]{}
```

The default is to show the year.

```
389 \DTMsetbool{german}{showyear}{true}
```

Define the german style.

```
390 \DTMnewstyle
391 {german}% label
392 {% date style
393   \renewcommand*{\DTMdisplaydate[4]}{%
394     \ifDTMshowdow
395       \ifnum##4>-1
396         \DTMifbool{german}{abbr}%
397         {\DTMgermanshortweekdayname{##4}}%
398         {\DTMgermanweekdayname{##4}}%
399         \DTMgermandowdaysep
400       \fi
401     \fi
402     %
403     \DTMifbool{german}{showdayofmonth}%
404     {\DTMgermanordinal{##3}\DTMgermandaymonthsep}%
405     {}%
406     %
407     \DTMifbool{german}{abbr}%
```

```

408     {\DTMgermanshortmonthname{##2}}%
409     {\DTMgermanmonthname{##2}}%
410     %
411     \DTMifbool{german}{showyear}%
412     {%
413         \DTMgermanmonthyearsep%
414         \DTMifbool{german}{abbr}%
415         {'\DTMtwdigits{##1}}%
416         {\number##1 }% space intended
417     }%
418     {}%
419 }%
420 \renewcommand*\DTMdisplaydate[4]{%
421     \ifDTMshowdow
422         \ifnum##4>-1
423             \DTMifbool{german}{abbr}%
424             {\DTMgermanshortweekdayname{##4}}%
425             {\DTMgermanweekdayname{##4}}%
426             \DTMgermandowdaysep
427         \fi
428     \fi
429     %
430     \DTMifbool{german}{showdayofmonth}%
431     {\DTMgermanordinal{##3}\DTMgermandaymonthsep}%
432     {}%
433     %
434     \DTMifbool{german}{abbr}%
435     {\DTMgermanshortmonthname{##2}}%
436     {\DTMgermanmonthname{##2}}%
437     %
438     \DTMifbool{german}{showyear}%
439     {%
440         \DTMgermanmonthyearsep%
441         \DTMifbool{german}{abbr}%
442         {'\DTMtwdigits{##1}}%
443         {\number##1 }% space intended
444     }%
445     {}%
446 }
447 }%
448 {% time style (use default)
449     \renewcommand*\DTMdisplaytime[3]{%
450         \DTMtwdigits{##1}%
451         \DTMgermantimesep\DTMtwdigits{##2}%
452         \ifDTMshowseconds\DTMgermantimesep\DTMtwdigits{##3}\fi
453     }%
454 }%
455 {% zone style
456     \DTMresetzones
457     \DTMgermanzonemaps
458     \renewcommand*\DTMdisplayzone[2]{%
459         \DTMifbool{german}{mapzone}%
460         {\DTMusezonemapordefault{##1}{##2}}%
461         {%
462             \ifnum##1<0\else\fi\DTMtwdigits{##1}%
463             \ifDTMshowzoneminutes\DTMgermantimesep\DTMtwdigits{##2}\fi

```

```

464     }%
465 }%
466 }%
467 {% full style
468 \renewcommand*{\DTMdisplay}[9]{%
469   \ifDTMshowdate
470     \DTMdisplaydate{##1}{##2}{##3}{##4}%
471     \DTMgermandatetimesep
472   \fi
473   \DTMdisplaytime{##5}{##6}{##7}%
474   \ifDTMshowzone
475     \DTMgermantimezonesep
476     \DTMdisplayzone{##8}{##9}%
477   \fi
478 }%
479 \renewcommand*{\DTMDisplay}[9]{%
480   \ifDTMshowdate
481     \DTMDisplaydate{##1}{##2}{##3}{##4}%
482     \DTMgermandatetimesep
483   \fi
484   \DTMdisplaytime{##5}{##6}{##7}%
485   \ifDTMshowzone
486     \DTMgermantimezonesep
487     \DTMdisplayzone{##8}{##9}%
488   \fi
489 }%
490 }%

```

Define numeric style.

```

491 \DTMnewstyle
492 {german-numeric}% label
493 {% date style
494   \renewcommand*{\DTMdisplaydate}[4]{%
495     \ifDTMshowdow
496       \ifnum##4>-1
497         \DTMifbool{german}{abbr}%
498         {\DTMgermanshortweekdayname{##4}}%
499         {\DTMgermanweekdayname{##4}}%
500         \DTMgermandowdaysep
501       \fi
502     \fi
503     %
504     \DTMifbool{german}{showdayofmonth}%
505     {%
506       \DTMtwodigits{##3}%
507       \DTMgermandatesep
508     }%
509     {}%
510     \DTMtwodigits{##2}%
511     \DTMgermandatesep%
512     \DTMifbool{german}{showyear}%
513     {%
514       \DTMifbool{german}{abbr}%
515       {\DTMtwodigits{##1}}%
516       {\number##1 }% space intended
517     }%
518     {}%

```

```

519 }%
520 \renewcommand*{\DTMdisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
521 }%
522 {% time style
523 \renewcommand*{\DTMdisplaytime}[3]{%
524 \DTMtwdigits{##1}%
525 \DTMgermantimesep\DTMtwdigits{##2}%
526 \ifDTMshowseconds\DTMgermantimesep\DTMtwdigits{##3}\fi
527 }%
528 }%
529 {% zone style
530 \DTMresetzones
531 \DTMgermanzonemaps
532 \renewcommand*{\DTMdisplayzone}[2]{%
533 \DTMifbool{german}{mapzone}%
534 {\DTMusedzonemapordefault{##1}{##2}}%
535 {%
536 \ifnum##1<0\else+\fi\DTMtwdigits{##1}%
537 \ifDTMshowzoneminutes\DTMgermantimesep\DTMtwdigits{##2}\fi
538 }%
539 }%
540 }%
541 {% full style
542 \renewcommand*{\DTMdisplay}[9]{%
543 \ifDTMshowdate
544 \DTMdisplaydate{##1}{##2}{##3}{##4}%
545 \DTMgermandatetimesep
546 \fi
547 \DTMdisplaytime{##5}{##6}{##7}%
548 \ifDTMshowzone
549 \DTMgermantimezonesep
550 \DTMdisplayzone{##8}{##9}%
551 \fi
552 }%
553 \renewcommand*{\DTMdisplay}{\DTMdisplay}%
554 }

```

`\DTMgermanzonemaps` The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

555 \newcommand*{\DTMgermanzonemaps}{%
556 \DTMdefzonemap{01}{00}{MEZ}%
557 \DTMdefzonemap{02}{00}{MESZ}%
558 }

```

Switch style according to the useregional setting.

```

559 \DTMifcaseregional
560 {% do nothing
561 {\DTMsetstyle{german}}
562 {\DTMsetstyle{german-numeric}}

```

Redefine `\dategerman` (or `\date(dialect)`) to prevent babel from resetting `\today`. (For this to work, babel must already have been loaded if it's required.)

```

563 \ifcsundef{date\CurrentTrackedDialect}
564 {%
565 \ifundef\dategerman
566 {% do nothing
567 }%

```

```

568 {%
569   \def\dategerman{%
570     \DTMifcaseregional
571     {}% do nothing
572     {\DTMsetstyle{german}}%
573     {\DTMsetstyle{german-numeric}}%
574   }%
575 }%
576 }%
577 {%
578   \csdef{date\CurrentTrackedDialect}{%
579     \DTMifcaseregional
580     {}% do nothing
581     {\DTMsetstyle{german}}%
582     {\DTMsetstyle{german-numeric}}
583   }%
584 }%

```

7 German localization (de-DE, datetime2-de-DE.1df)

Identify Module

585 \ProvidesDateTimeModule{de-DE}[2017/10/03 v2.0]

Require the basic German module

586 \RequireDateTimeModule{german}

Allow the user a way of configuring the de-DE and de-DE-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

\DTMdeDEdowdaysep	The separator between weekday and day 587 \newcommand*{\DTMdeDEdowdaysep}{, \space}
\DTMdeDEdaymonthsep	The separator between the day and month for the text format. 588 \newcommand*{\DTMdeDEdaymonthsep}{. \DTMtexorpdfstring{\protect~}{\space}}
\DTMdeDEmonthyearsep	The separator between the month and year for the text format. 589 \newcommand*{\DTMdeDEmonthyearsep}{\space}
\DTMdeDEdatetimesep	The separator between the date and time blocks in the full format (either text or numeric). 590 \newcommand*{\DTMdeDEdatetimesep}{, \space}
\DTMdeDEtimezonesep	The separator between the time and zone blocks in the full format (either text or numeric). 591 \newcommand*{\DTMdeDEtimezonesep}{\space}
\DTMdeDEdatesep	The separator for the numeric date format. 592 \newcommand*{\DTMdeDEdatesep}{. }
\DTMdeDEtimesep	The separator for the numeric time format. 593 \newcommand*{\DTMdeDEtimesep}{: }

Provide keys that can be used in \DTMlangsetup to set these separators.

```

594 \DTMdefkey{de-DE}{dowdaysep}{\renewcommand*{\DTMdeDEdowdaysep}{#1}}
595 \DTMdefkey{de-DE}{daymonthsep}{\renewcommand*{\DTMdeDEdaymonthsep}{#1}}
596 \DTMdefkey{de-DE}{monthyearsep}{\renewcommand*{\DTMdeDEmonthyearsep}{#1}}
597 \DTMdefkey{de-DE}{datetimesep}{\renewcommand*{\DTMdeDEdatetimesep}{#1}}

```

```

598 \DTMdefkey{de-DE}{timezonesep}{\renewcommand*\DTMdeDEtimezonesep}{#1}}
599 \DTMdefkey{de-DE}{datesep}{\renewcommand*\DTMdeDEdatesep}{#1}}
600 \DTMdefkey{de-DE}{timesep}{\renewcommand*\DTMdeDEtimesep}{#1}}

```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
601 \DTMdefboolkey{de-DE}{abbr}[true]{}

```

The default is full name

```
602 \DTMsetbool{de-DE}{abbr}{false}

```

Define a boolean key that determines if the time zone mappings should be used.

```
603 \DTMdefboolkey{de-DE}{mapzone}[true]{}

```

The default is to use mappings.

```
604 \DTMsetbool{de-DE}{mapzone}{true}

```

Define a boolean key that determines if the day of month should be displayed.

```
605 \DTMdefboolkey{de-DE}{showdayofmonth}[true]{}

```

The default is to show the day of month.

```
606 \DTMsetbool{de-DE}{showdayofmonth}{true}

```

Define a boolean key that determines if the year should be displayed.

```
607 \DTMdefboolkey{de-DE}{showyear}[true]{}

```

The default is to show the year.

```
608 \DTMsetbool{de-DE}{showyear}{true}

```

Define the de-DE style

```

609 \DTMnewstyle
610 {de-DE}% label
611 {% date style
612   \renewcommand*\DTMdisplaydate[4]{%
613     \ifDTMshowdow
614       \ifnum##4>-1
615         \DTMifbool{de-DE}{abbr}%
616         {\DTMgermanshortweekdayname{##4}}%
617         {\DTMgermanweekdayname{##4}}%
618         \DTMdeDEdowdaysep
619       \fi
620     \fi
621     %
622     \DTMifbool{de-DE}{showdayofmonth}%
623     {\DTMgermanordinal{##3}\DTMdeDEdaymonthsep}%
624     }%
625     %
626     \DTMifbool{de-DE}{abbr}%
627     {\DTMgermanshortmonthname{##2}}%
628     {\DTMgermanmonthname{##2}}%
629     %
630     \DTMifbool{de-DE}{showyear}%
631     {%
632       \DTMdeDEmonthyearsep%
633       \DTMifbool{de-DE}{abbr}%
634       {'\DTMtwdigits{##1}}%
635       {\number##1 }% space intended
636     }%
637   }%
638 }%

```

```

639 \renewcommand*\DTMDisplaydate[4]{%
640   \ifDTMshowdow
641     \ifnum##4>-1
642       \DTMifbool{de-DE}{abbr}%
643       {\DTMgermanshortweekdayname{##4}}%
644       {\DTMgermanweekdayname{##4}}%
645       \DTMdeDEdowdaysep
646     \fi
647   \fi
648   %
649   \DTMifbool{de-DE}{showdayofmonth}%
650   {\DTMgermanordinal{##3}\DTMdeDEdaymonthsep}%
651   }%
652   %
653   \DTMifbool{de-DE}{abbr}%
654   {\DTMgermanshortmonthname{##2}}%
655   {\DTMgermanmonthname{##2}}%
656   %
657   \DTMifbool{de-DE}{showyear}%
658   {%
659     \DTMdeDEmonthyearsep%
660     \DTMifbool{de-DE}{abbr}%
661     {'\DTMtwdigits{##1}}%
662     {\number##1 }% space intended
663   }%
664   }%
665 }
666}%
667{% time style (use default)
668 \renewcommand*\DTMdisplaytime[3]{%
669   \DTMtwdigits{##1}%
670   \DTMdeDEtimesep\DTMtwdigits{##2}%
671   \ifDTMshowseconds\DTMdeDEtimesep\DTMtwdigits{##3}\fi
672 }%
673}%
674{% zone style
675 \DTMresetzones
676 \DTMgermanzonemaps
677 \renewcommand*\DTMdisplayzone[2]{%
678   \DTMifbool{de-DE}{mapzone}%
679   {\DTMuseumzonemapordefault{##1}{##2}}%
680   {%
681     \ifnum##1<0\else+\fi\DTMtwdigits{##1}%
682     \ifDTMshowzoneminutes\DTMdeDEtimesep\DTMtwdigits{##2}\fi
683   }%
684 }%
685}%
686{% full style
687 \renewcommand*\DTMdisplay[9]{%
688   \ifDTMshowdate
689     \DTMdisplaydate{##1}{##2}{##3}{##4}%
690     \DTMdeDEdatetimesep
691   \fi
692   \DTMdisplaytime{##5}{##6}{##7}%
693   \ifDTMshowzone
694     \DTMdeDEtimezonesep

```

```

695     \DTMdisplayzone{##8}{##9}%
696   \fi
697 }%
698 \renewcommand*{\DTMDisplay}[9]{%
699   \ifDTMshowdate
700     \DTMdisplaydate{##1}{##2}{##3}{##4}%
701     \DTMdeDEdatetimesep
702   \fi
703   \DTMdisplaytime{##5}{##6}{##7}%
704   \ifDTMshowzone
705     \DTMdeDEtimezonesep
706     \DTMdisplayzone{##8}{##9}%
707   \fi
708 }%
709 }%

```

Define numeric style.

```

710 \DTMnewstyle
711 {de-DE-numeric}% label
712 {% date style
713   \renewcommand*{\DTMdisplaydate}[4]{%
714     \ifDTMshowdow
715       \ifnum##4>-1
716         \DTMifbool{de-DE}{abbr}%
717         {\DTMgermanshortweekdayname{##4}}%
718         {\DTMgermanweekdayname{##4}}%
719         \DTMdeDEdowdaysep
720       \fi
721     \fi
722     %
723     \DTMifbool{de-DE}{showdayofmonth}%
724     {%
725       \DTMtwodigits{##3}%
726       \DTMdeDEdatesep
727     }%
728     {%
729       \DTMtwodigits{##2}%
730       \DTMdeDEdatesep%
731       \DTMifbool{de-DE}{showyear}%
732       {%
733         \DTMifbool{de-DE}{abbr}%
734         {\DTMtwodigits{##1}}%
735         {\number##1 }% space intended
736       }%
737     }%
738   }%
739   \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
740 }%
741 {% time style
742   \renewcommand*{\DTMdisplaytime}[3]{%
743     \DTMtwodigits{##1}%
744     \DTMdeDEtimesep\DTMtwodigits{##2}%
745     \ifDTMshowseconds\DTMdeDEtimesep\DTMtwodigits{##3}\fi
746   }%
747 }%
748 {% zone style
749   \DTMresetzones

```

```

750 \DTMgermanzonemaps
751 \renewcommand*{\DTMdisplayzone}[2]{%
752   \DTMifbool{de-DE}{mapzone}%
753   {\DTMuseumzonemapordefault{##1}{##2}}%
754   {%
755     \ifnum##1<0\else+\fi\DTMtwdigits{##1}%
756     \ifDTMshowzoneminutes\DTMgermantimesep\DTMtwdigits{##2}\fi
757   }%
758 }%
759 }%
760 {% full style
761   \renewcommand*{\DTMdisplay}[9]{%
762     \ifDTMshowdate
763       \DTMdisplaydate{##1}{##2}{##3}{##4}%
764       \DTMdeDEdatetimesep
765       \fi
766       \DTMdisplaytime{##5}{##6}{##7}%
767       \ifDTMshowzone
768         \DTMdeDEtimezonesep
769         \DTMdisplayzone{##8}{##9}%
770       \fi
771     }%
772   \renewcommand*{\DTMDisplay}{\DTMdisplay}%
773 }

```

Switch style according to the useregional setting.

```

774 \DTMifcaseregional
775 {}% do nothing
776 {\DTMsetstyle{de-DE}}
777 {\DTMsetstyle{de-DE-numeric}}

```

Redefine \dategerman (or \date(*dialect*)) to prevent babel from resetting \today. (For this to work, babel must already have been loaded if it's required.)

```

778 \ifcsundef{date\CurrentTrackedDialect}
779 {%
780   \ifundef\dategerman
781   {% do nothing
782   }%
783   {%
784     \def\dategerman{%
785       \DTMifcaseregional
786       {}% do nothing
787       {\DTMsetstyle{german}}%
788       {\DTMsetstyle{german-numeric}}%
789     }%
790   }%
791 }%
792 {%
793   \csdef{date\CurrentTrackedDialect}{%
794     \DTMifcaseregional
795     {}% do nothing
796     {\DTMsetstyle{de-DE}}%
797     {\DTMsetstyle{de-DE-numeric}}
798   }%
799 }%

```

8 Austrian German localization (de-AT, datetime2-de-AT.1df)

Identify Module

```
800 \ProvidesDateTimeModule{de-AT}[2017/10/03 v2.0]
```

Require the basic German module

```
801 \RequireDateTimeModule{german}
```

Allow the user a way of configuring the de-AT and de-AT-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

```
\DTMdeATdowdaysep The separator between weekday and day
802 \newcommand*{\DTMdeATdowdaysep}{, \space}

\DTMdeATdaymonthsep The separator between the day and month for the text format.
803 \newcommand*{\DTMdeATdaymonthsep}{. \DTMtexorpdfstring{\protect~}{\space}}

\DTMdeATmonthyearsep The separator between the month and year for the text format.
804 \newcommand*{\DTMdeATmonthyearsep}{\space}

\DTMdeATdatetimesep The separator between the date and time blocks in the full format (either text or numeric).
805 \newcommand*{\DTMdeATdatetimesep}{, \space}

\DTMdeATtimezonesep The separator between the time and zone blocks in the full format (either text or numeric).
806 \newcommand*{\DTMdeATtimezonesep}{\space}

\DTMdeATdatesep The separator for the numeric date format.
807 \newcommand*{\DTMdeATdatesep}{-}

\DTMdeATtimesep The separator for the numeric time format.
808 \newcommand*{\DTMdeATtimesep}{:}
```

Provide keys that can be used in \DTMlangsetup to set these separators.

```
809 \DTMdefkey{de-AT}{dowdaysep}{\renewcommand*{\DTMdeATdowdaysep}{#1}}
810 \DTMdefkey{de-AT}{daymonthsep}{\renewcommand*{\DTMdeATdaymonthsep}{#1}}
811 \DTMdefkey{de-AT}{monthyearsep}{\renewcommand*{\DTMdeATmonthyearsep}{#1}}
812 \DTMdefkey{de-AT}{datetimesep}{\renewcommand*{\DTMdeATdatetimesep}{#1}}
813 \DTMdefkey{de-AT}{timezonesep}{\renewcommand*{\DTMdeATtimezonesep}{#1}}
814 \DTMdefkey{de-AT}{datesep}{\renewcommand*{\DTMdeATdatesep}{#1}}
815 \DTMdefkey{de-AT}{timesep}{\renewcommand*{\DTMdeATtimesep}{#1}}
```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
816 \DTMdefboolkey{de-AT}{abbr}[true]{}
```

The default is full name

```
817 \DTMsetbool{de-AT}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
818 \DTMdefboolkey{de-AT}{mapzone}[true]{}
```

The default is to use mappings.

```
819 \DTMsetbool{de-AT}{mapzone}{true}
```

Define a boolean key that determines if the day of month should be displayed.

```
820 \DTMdefboolkey{de-AT}{showdayofmonth}[true]{}
```

The default is to show the day of month.

```
821 \DTMsetbool{de-AT}{showdayofmonth}{true}
```

Define a boolean key that determines if the year should be displayed.

```
822 \DTMdefboolkey{de-AT}{showyear}[true]{}
```

The default is to show the year.

```
823 \DTMsetbool{de-AT}{showyear}{true}
```

Define the de-AT style

```
824 \DTMnewstyle
825 {de-AT}% label
826 {% date style
827   \renewcommand*\DTMdisplaydate[4]{%
828     \ifDTMshowdow
829       \ifnum##4>-1
830         \DTMifbool{de-AT}{abbr}%
831         {\DTMgermanshortweekdayname{##4}}%
832         {\DTMgermanweekdayname{##4}}%
833         \DTMdeATdowdaysep
834       \fi
835     \fi
836     %
837     \DTMifbool{de-AT}{showdayofmonth}%
838     {\DTMgermanordinal{##3}\DTMdeATdaymonthsep}%
839     {}%
840     %
841     \DTMifbool{de-AT}{abbr}%
842     {\DTMdeATshortmonthname{##2}}%
843     {\DTMdeATmonthname{##2}}%
844     %
845     \DTMifbool{de-AT}{showyear}%
846     {%
847       \DTMdeATmonthyearsep%
848       \number##1 % space intended
849     }%
850     {}%
851   }%
852   \renewcommand*\DTMdisplaydate[4]{%
853     \ifDTMshowdow
854       \ifnum##4>-1
855         \DTMifbool{de-AT}{abbr}%
856         {\DTMgermanshortweekdayname{##4}}%
857         {\DTMgermanweekdayname{##4}}%
858         \DTMdeATdowdaysep
859       \fi
860     \fi
861     %
862     \DTMifbool{de-AT}{showdayofmonth}%
863     {\DTMgermanordinal{##3}\DTMdeATdaymonthsep}%
864     {}%
865     %
866     \DTMifbool{de-AT}{abbr}%
867     {\DTMdeATshortmonthname{##2}}%
868     {\DTMdeATmonthname{##2}}%
869     %
870     \DTMifbool{de-AT}{showyear}%
871     {%
872       \DTMdeATmonthyearsep%
873       \number##1 % space intended
```

```

874     }%
875     {}%
876 }
877 }%
878 {% time style (use default)
879     \renewcommand*{\DTMdisplaytime[3]}{%
880         \DTMtwdigits{##1}%
881         \DTMdeATtimesep\DTMtwdigits{##2}%
882         \ifDTMshowseconds\DTMdeATtimesep\DTMtwdigits{##3}\fi
883     }%
884 }%
885 {% zone style
886     \DTMresetzones
887     \DTMgermanzonemaps
888     \renewcommand*{\DTMdisplayzone}[2]{%
889         \DTMifbool{de-AT}{mapzone}%
890         {\DTMuseumaportdefault{##1}{##2}}%
891         {%
892             \ifnum##1<0\else+\fi\DTMtwdigits{##1}%
893             \ifDTMshowzoneminutes\DTMdeATtimesep\DTMtwdigits{##2}\fi
894         }%
895     }%
896 }%
897 {% full style
898     \renewcommand*{\DTMdisplay}[9]{%
899         \ifDTMshowdate
900             \DTMdisplaydate{##1}{##2}{##3}{##4}%
901             \DTMdeATdatetimesep
902             \fi
903             \DTMdisplaytime{##5}{##6}{##7}%
904             \ifDTMshowzone
905                 \DTMdeATtimezonesep
906                 \DTMdisplayzone{##8}{##9}%
907             \fi
908         }%
909     \renewcommand*{\DTMDisplay}[9]{%
910         \ifDTMshowdate
911             \DTMDisplaydate{##1}{##2}{##3}{##4}%
912             \DTMdeATdatetimesep
913             \fi
914             \DTMdisplaytime{##5}{##6}{##7}%
915             \ifDTMshowzone
916                 \DTMdeATtimezonesep
917                 \DTMdisplayzone{##8}{##9}%
918             \fi
919         }%
920 }%

```

Define numeric style.

```

921 \DTMnewstyle
922 {de-AT-numeric}% label
923 {% date style
924     \renewcommand*{\DTMdisplaydate[4]}{%
925         \DTMifbool{de-AT}{showyear}%
926         {%
927             \number##1 % space intended
928             \DTMdeATdatesep%

```

```

929 }%
930 {}%
931 %
932 \DTMt看odigits{##2}%
933 %
934 \DTMifbool{de-AT}{showdayofmonth}%
935 {%
936     \DTMdeATdatesep%
937     \DTMt看odigits{##3}%
938 }%
939 {}%
940 }%
941 \renewcommand*{\DTMdisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
942 }%
943 {% time style
944 \renewcommand*{\DTMdisplaytime}[3]{%
945     \DTMt看odigits{##1}%
946     \DTMdeATtimesep\DTMt看odigits{##2}%
947     \ifDTMshowseconds\DTMdeATtimesep\DTMt看odigits{##3}\fi
948 }%
949 }%
950 {% zone style
951 \DTMresetzones
952 \DTMgermanzonemaps
953 \renewcommand*{\DTMdisplayzone}[2]{%
954     \DTMifbool{de-AT}{mapzone}%
955     {\DTMusezonemapordefault{##1}{##2}}%
956     {%
957         \ifnum##1<0\else+\fi\DTMt看odigits{##1}%
958         \ifDTMshowzoneminutes\DTMgermantimesep\DTMt看odigits{##2}\fi
959     }%
960 }%
961 }%
962 {% full style
963 \renewcommand*{\DTMdisplay}[9]{%
964     \ifDTMshowdate
965         \DTMdisplaydate{##1}{##2}{##3}{##4}%
966         \DTMdeATdatetimesep
967     \fi
968     \DTMdisplaytime{##5}{##6}{##7}%
969     \ifDTMshowzone
970         \DTMdeATtimezonesep
971         \DTMdisplayzone{##8}{##9}%
972     \fi
973 }%
974 \renewcommand*{\DTMdisplay}{\DTMdisplay}%
975 }

```

Switch style according to the useregional setting.

```

976 \DTMifcaseregional
977 {}% do nothing
978 {\DTMsetstyle{de-AT}}
979 {\DTMsetstyle{de-AT-numeric}}

```

Redefine \dategerman (or \date(*dialect*)) to prevent babel from resetting \today. (For this to work, babel must already have been loaded if it's required.)

```

980 \ifcsundef{date\CurrentTrackedDialect}

```

```

981 {%
982   \ifundef\dategerman
983   {% do nothing
984   }%
985   {%
986     \def\dategerman{%
987       \DTMifcaseregional
988       {% do nothing
989       {\DTMsetstyle{german}}%
990       {\DTMsetstyle{german-numeric}}%
991     }%
992   }%
993 }%
994 {%
995   \csdef{date\CurrentTrackedDialect}{%
996     \DTMifcaseregional
997     {% do nothing
998     {\DTMsetstyle{de-AT}}%
999     {\DTMsetstyle{de-AT-numeric}}
1000   }%
1001 }%

```

9 Swiss German localization (de-CH, datetime2-de-CH.1df)

Identify Module

```
1002 \ProvidesDateTimeModule{de-CH}[2017/10/03 v2.0]
```

Require the basic German module

```
1003 \RequireDateTimeModule{german}
```

Allow the user a way of configuring the de-CH and de-CH-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

\DTMdeCHdowdaysep	The separator between weekday and day 1004 \newcommand*{\DTMdeCHdowdaysep}{, \space}
\DTMdeCHdaymonthsep	The separator between the day and month for the text format. 1005 \newcommand*{\DTMdeCHdaymonthsep}{.\DTMtexorpdfstring{\protect~}{\space}}
\DTMdeCHmonthyearsep	The separator between the month and year for the text format. 1006 \newcommand*{\DTMdeCHmonthyearsep}{\space}
\DTMdeCHdatetimesep	The separator between the date and time blocks in the full format (either text or numeric). 1007 \newcommand*{\DTMdeCHdatetimesep}{, \space}
\DTMdeCHtimezonesep	The separator between the time and zone blocks in the full format (either text or numeric). 1008 \newcommand*{\DTMdeCHtimezonesep}{\space}
\DTMdeCHdatesep	The separator for the numeric date format. 1009 \newcommand*{\DTMdeCHdatesep}{. }
\DTMdeCHtimesep	The separator for the numeric time format. 1010 \newcommand*{\DTMdeCHtimesep}{. }

Provide keys that can be used in \DTMlangsetup to set these separators.

```
1011 \DTMdefkey{de-CH}{dowdaysep}{\renewcommand*\DTMdeCHdowdaysep}{#1}}
1012 \DTMdefkey{de-CH}{daymonthsep}{\renewcommand*\DTMdeCHdaymonthsep}{#1}}
1013 \DTMdefkey{de-CH}{monthyearsep}{\renewcommand*\DTMdeCHmonthyearsep}{#1}}
1014 \DTMdefkey{de-CH}{datetimesep}{\renewcommand*\DTMdeCHdatetimesep}{#1}}
1015 \DTMdefkey{de-CH}{timezonesep}{\renewcommand*\DTMdeCHtimezonesep}{#1}}
1016 \DTMdefkey{de-CH}{datesep}{\renewcommand*\DTMdeCHdatesep}{#1}}
1017 \DTMdefkey{de-CH}{timesep}{\renewcommand*\DTMdeCHtimesep}{#1}}
```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
1018 \DTMdefboolkey{de-CH}{abbr}[true]{}
```

The default is full name

```
1019 \DTMsetbool{de-CH}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
1020 \DTMdefboolkey{de-CH}{mapzone}[true]{}
```

The default is to use mappings.

```
1021 \DTMsetbool{de-CH}{mapzone}{true}
```

Define a boolean key that determines if the day of month should be displayed.

```
1022 \DTMdefboolkey{de-CH}{showdayofmonth}[true]{}
```

The default is to show the day of month.

```
1023 \DTMsetbool{de-CH}{showdayofmonth}{true}
```

Define a boolean key that determines if the year should be displayed.

```
1024 \DTMdefboolkey{de-CH}{showyear}[true]{}
```

The default is to show the year.

```
1025 \DTMsetbool{de-CH}{showyear}{true}
```

Define the de-CH style

```
1026 \DTMnewstyle
1027 {de-CH}% label
1028 {% date style
1029   \renewcommand*\DTMdisplaydate[4]{%
1030     \ifDTMshowdow
1031       \ifnum##4>-1
1032         \DTMifbool{de-CH}{abbr}%
1033         {\DTMgermanshortweekdayname{##4}}%
1034         {\DTMgermanweekdayname{##4}}%
1035         \DTMdeCHdowdaysep
1036       \fi
1037     \fi
1038     %
1039     \DTMifbool{de-CH}{showdayofmonth}%
1040     {\DTMgermanordinal{##3}\DTMdeCHdaymonthsep}%
1041     {}%
1042     %
1043     \DTMifbool{de-CH}{abbr}%
1044     {\DTMdeCHshortmonthname{##2}}%
1045     {\DTMgermanmonthname{##2}}%
1046     %
1047     \DTMifbool{de-CH}{showyear}%
1048     {%
1049       \DTMdeCHmonthyearsep%
1050       \number##1 % space intended
```

```

1051 }%
1052 {}%
1053 }%
1054 \renewcommand*{\DTMDisplaydate[4]{%
1055     \ifDTMshowdow
1056         \ifnum##4>-1
1057             \DTMifbool{de-CH}{abbr}%
1058             {\DTMgermanshortweekdayname{##4}}%
1059             {\DTMgermanweekdayname{##4}}%
1060             \DTMdeCHdowdaysep
1061         \fi
1062     \fi
1063     %
1064     \DTMifbool{de-CH}{showdayofmonth}%
1065     {\DTMgermanordinal{##3}\DTMdeCHdaymonthsep}%
1066     {}%
1067     %
1068     \DTMifbool{de-CH}{abbr}%
1069     {\DTMdeCHshortmonthname{##2}}%
1070     {\DTMgermanmonthname{##2}}%
1071     %
1072     \DTMifbool{de-CH}{showyear}%
1073     {%
1074         \DTMdeCHmonthyearsep%
1075         \number##1 % space intended
1076     }%
1077     {}%
1078 }
1079 }%
1080 {% time style (use default)
1081     \renewcommand*{\DTMdisplaytime[3]{%
1082         \DTMtwdigits{##1}%
1083         \DTMdeCHtimesep\DTMtwdigits{##2}%
1084         \ifDTMshowseconds\DTMdeCHtimesep\DTMtwdigits{##3}\fi\space%
1085         Uhr%
1086     }%
1087 }%
1088 {% zone style
1089     \DTMresetzones
1090     \DTMgermanzonemaps
1091     \renewcommand*{\DTMdisplayzone}[2]{%
1092         \DTMifbool{de-CH}{mapzone}%
1093         {\DTMusezonemapordefault{##1}{##2}}%
1094         {%
1095             \ifnum##1<0\else+\fi\DTMtwdigits{##1}%
1096             \ifDTMshowzoneminutes\DTMdeCHtimesep\DTMtwdigits{##2}\fi
1097         }%
1098     }%
1099 }%
1100 {% full style
1101     \renewcommand*{\DTMdisplay}[9]{%
1102         \ifDTMshowdate
1103             \DTMdisplaydate{##1}{##2}{##3}{##4}%
1104             \DTMdeCHdatetimesep
1105         \fi
1106         \DTMdisplaytime{##5}{##6}{##7}%

```

```

1107     \ifDTMshowzone
1108         \DTMdeCHtimezonessep
1109         \DTMdisplayzone{##8}{##9}%
1110     \fi
1111 }%
1112 \renewcommand*\DTMDisplay}[9]{%
1113     \ifDTMshowdate
1114         \DTMDisplaydate{##1}{##2}{##3}{##4}%
1115         \DTMdeCHdatetimesep
1116     \fi
1117     \DTMdisplaytime{##5}{##6}{##7}%
1118     \ifDTMshowzone
1119         \DTMdeCHtimezonessep
1120         \DTMdisplayzone{##8}{##9}%
1121     \fi
1122 }%
1123 }%

```

Define numeric style.

```

1124 \DTMnewstyle
1125 {de-CH-numeric}% label
1126 {% date style
1127     \renewcommand*\DTMdisplaydate[4]{%
1128         \ifDTMshowdow
1129             \ifnum##4>-1
1130                 \DTMifbool{de-CH}{abbr}%
1131                 {\DTMgermanshortweekdayname{##4}}%
1132                 {\DTMgermanweekdayname{##4}}%
1133 \DTMdeCHdowdaysep
1134         \fi
1135     \fi
1136     %
1137     \DTMifbool{de-CH}{showdayofmonth}%
1138     {%
1139         \DTMtwodigits{##3}%
1140         \DTMdeCHdatesep
1141     }%
1142     {%
1143         \DTMtwodigits{##2}%
1144         \DTMdeCHdatesep%
1145         \DTMifbool{de-CH}{showyear}%
1146         {%
1147             \number##1 % space intended
1148         }%
1149     }%
1150 }%
1151 \renewcommand*\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1152 }%
1153 {% time style
1154     \renewcommand*\DTMdisplaytime[3]{%
1155         \DTMtwodigits{##1}%
1156         \DTMdeCHtimesep\DTMtwodigits{##2}%
1157         \ifDTMshowseconds\DTMdeCHtimesep\DTMtwodigits{##3}\fi\space%
1158         Uhr%
1159     }%
1160 }%
1161 {% zone style

```

```

1162 \DTMresetzones
1163 \DTMgermanzonemaps
1164 \renewcommand*{\DTMdisplayzone}[2]{%
1165   \DTMifbool{de-CH}{mapzone}%
1166   {\DTMuseumaportdefault{##1}{##2}}%
1167   {%
1168     \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1169     \ifDTMshowzoneminutes\DTMgermantimesep\DTMtwodigits{##2}\fi
1170   }%
1171 }%
1172 }%
1173 {% full style
1174 \renewcommand*{\DTMdisplay}[9]{%
1175   \ifDTMshowdate
1176     \DTMdisplaydate{##1}{##2}{##3}{##4}%
1177     \DTMdeCHdatetimesep
1178   \fi
1179   \DTMdisplaytime{##5}{##6}{##7}%
1180   \ifDTMshowzone
1181     \DTMdeCHtimezonesep
1182     \DTMdisplayzone{##8}{##9}%
1183   \fi
1184 }%
1185 \renewcommand*{\DTMDisplay}{\DTMdisplay}%
1186 }

```

Switch style according to the useregional setting.

```

1187 \DTMifcaseregional
1188 {% do nothing
1189 {\DTMsetstyle{de-CH}}
1190 {\DTMsetstyle{de-CH-numeric}}

```

Redefine \dategerman (or \date(*dialect*)) to prevent babel from resetting \today. (For this to work, babel must already have been loaded if it's required.)

```

1191 \ifcsundef{date\CurrentTrackedDialect}
1192 {%
1193   \ifundef\dategerman
1194   {% do nothing
1195   }%
1196   {%
1197     \def\dategerman{%
1198       \DTMifcaseregional
1199       {% do nothing
1200       {\DTMsetstyle{german}}%
1201       {\DTMsetstyle{german-numeric}}%
1202     }%
1203   }%
1204 }%
1205 {%
1206 \csdef{date\CurrentTrackedDialect}{%
1207   \DTMifcaseregional
1208   {% do nothing
1209   {\DTMsetstyle{de-CH}}%
1210   {\DTMsetstyle{de-CH-numeric}}
1211   }%
1212 }%

```

Change History

1.0	General: Initial release	7, 10, 14	names implemented	7, 11
1.1	General: fixed bug in \DTMDisplaydate . . .	15	\DTMdeATshortmonthname: Austrian short month names implemented	9, 12
1.2	\DTMgermanshortmonthname: Short month names implemented	8, 12	\DTMdeCHshortmonthname: Swiss German short month names implemented . . .	9, 13
	\DTMgermanshortweekdayname: Short weekday names implemented	10, 14	\DTMgermanshortmonthname: Short month names fixed	8, 12
	\DTMgermanzonemaps: German time zone names (ME[S]Z)	18	\DTMgermanshortweekdayname: Short weekday names fixed	10, 14
	General: Day of week implemented . . .	15, 17	General: Austrian German localization added	24
	Short month names implemented	15	Bugfix: month-year-separator	17
	Short weekday names implemented	15	German localization added	19
2.0	\DTMdeATmonthname: Austrian month		Swiss German localization added	28

Index

D		\DTMdeDEmonthyearsep	19
\DTMdeATdatesep	24	\DTMdeDEtimesep	19
\DTMdeATdatetimesep	24	\DTMdeDEtimezonesep	19
\DTMdeATdaymonthsep	24	\DTMgermandatesep	15
\DTMdeATdowdaysep	24	\DTMgermandatetimesep	14
\DTMdeATmonthname	7, 11	\DTMgermandaymonthsep	14
\DTMdeATmonthyearsep	24	\DTMgermandowdaysep	14
\DTMdeATshortmonthname	9, 12	\DTMgermanmonthname	7, 11
\DTMdeATtimesep	24	\DTMgermanmonthyearsep	14
\DTMdeATtimezonesep	24	\DTMgermanordinal	7, 10
\DTMdeCHdatesep	28	\DTMgermanshortmonthname	8, 12
\DTMdeCHdatetimesep	28	\DTMgermanshortweekdayname	10, 14
\DTMdeCHdaymonthsep	28	\DTMgermantimesep	15
\DTMdeCHdowdaysep	28	\DTMgermantimezonesep	14
\DTMdeCHmonthyearsep	28	\DTMgermanweekdayname	10, 13
\DTMdeCHshortmonthname	9, 13	\DTMgermanzonemaps	18
\DTMdeCHtimesep	28		
\DTMdeCHtimezonesep	28	S	
\DTMdeDEdatesep	19	showdow	4–6
\DTMdeDEdatetimesep	19		
\DTMdeDEdaymonthsep	19	U	
\DTMdeDEdowdaysep	19	useregional	1, 4, 18, 23, 27, 32